Formulating a Greener World®

SoluJET® Ultra 3000

High performance ink for non-porous media



Mylan GROUP
Formulating a Greener World®

Vietnam Value

SYSTEM CERTIFICATION ISO 14001 SGS

UKAS ENVIRONMENTAL MANAGEMENT 005

GUARDIAN INDEPENDENT CERTIFICATION ISO 9001 : 2015

UKAS QUALITY MANAGEMENT 045

TECHNICAL DATA SHEET

SoluJET® Ultra 3000 black solvent TIJ 2.5 Ink is specifically designed for track & trace coding, marking, and other high-productivity industrial packaging applications.
This ink delivers fast drying, excellent adhesion on common plastic substrates, and outstanding print sharpness across a wide range of materials, including PET, PVC, PA, OPP, and metalized foils.

Technical Specifications

	SoluJET® Ultra 3000 Print Cartridge
Ink type	Black dye solvent ink
Print cartridge type	HP 45si
Resolution	Up to 600 dpi, recommended 300 × 300 dpi
Nozzle count	300
Print swath	12.7 mm
Firing voltage	9.0 V
Fire pulse width	2.0 µs
Pulse warming	OFF
Decap time	Up to 1 h
Drying time	1 - 3 s at 300 × 300 dpi
Throw distance	Up to 5 mm
Average delivered ink	35 mL (vertical) and 33 mL (horizontal)
Average drop volume	43 pL
Operating conditions	15 °C to 35 °C, 45% to 80% RH
Shipping / storage temperature	10 °C to 30 °C
Best before	9 months from filling date

Cartridge Shipping & Storage

- The cartridge should be stored in vacuum sealed pouch until used.
- Use the cartridge within two weeks of removing it from vacuum sealed pouch for best performance.
- Store the cartridge with a clip placed over the printhead. Horizontal position is recommend.
- Refer to Safety Data Sheet for more information.

Cartridge Maintenance & Handling

- Use a lint-free cloth moistened with ethanol (> 98%) to clean the cartridge printhead.
- Holding the cartridge printhead face down, gently press the printhead on a lint-free cloth to allow ink to wick out. Then, slowly and lightly wipe across the tip of the long edge.
- Do not shake the cartridge.

Ordering Information

Product number	**Product description**
U300042A	SoluJET® Ultra 3000 Print Cartridge

MYLAN GROUP
Long Duc Industrial Park, Long Duc Ward, Vinh Long Province, Vietnam
Tel.: +84 294 3846 997 - Fax: +84 294 3846 998
Email: info@mylangroup.com
Website: www.mylangroup.com